



NC Sturgeon Safety Management System			Doc No:	HAZASID
			Initial Issue Date	02/2016
HAZARD IDENTIFICATION AND ASSESSMENT			Revision Date:	Initial Version
			Revision No.	0
			Next Revision Date:	TBD
Preparation: Safety Mgr	Authority: President	Issuing Dept: Safety	Page:	Page 1 of 7

Purpose

- To provide guidelines for identifying, assessing and controlling workplace hazards;
- To ensure the potential hazards of new processes and materials are identified before they are introduced into the workplace;
- To identify the jobs/tasks which require risk assessment.

Key Responsibilities

As specified within this program.

NC Sturgeon must assess a work site and identify existing or potential hazards before work begins at the work site or prior to the construction of a new work site

Hazard and Risk Identification

The hazard identification process is used for routine and non-routine activities as well as new processes, changes in operation, products or services as applicable.

The Safety Manager shall conduct a baseline worksite hazard assessment which is a formal process in place to identify the various tasks that are to be performed and the accompanying identified potential hazards. The results are included in a report of the results of the hazard assessment and the methods used to control or eliminate the hazards identified. The hazard assessment report must be signed and have the date on it.

Inputs into the baseline hazard identification include, but are not limited to:

- Scope of work;
- Legal and other requirements;
- Previous incidents and non-conformances;
- Sources of energy, contaminants and other environmental conditions that can cause injury;
- Walk through of work environment;

Hazards identifications (as examples) are to include:

- Working Alone
- Thermal Exposure
- Isolation of Energy
- Hearing Protection
- Musculoskeletal Disorders
- Bloodborne Pathogens
- Confined Spaces



NC Sturgeon Safety Management System	Doc No:	HAZASID
	Initial Issue Date	02/2016
	Revision Date:	Initial Version
	Revision No.	0

HAZARD IDENTIFICATION AND ASSESSMENT			Revision No.	0
			Next Revision Date:	TBD
Preparation: Safety Mgr	Authority: President	Issuing Dept: Safety	Page:	Page 2 of 7

- Driving
- General Safety Precautions
- And any other established policy or procedure by **NC Sturgeon**
- Any other site specific work scope

NC Sturgeon has a formal process for identifying potential hazards. Processes are in place to identify potential hazards by the use of JSA's, JHA's, facility wide or area specific analysis/inspections.

All identified hazards are assessed for risk and risk controls are assigned within the worksite hazard assessment for that specific hazard.

Employees and/or sub-contractors are actively involved in the hazard identification process. The **NC Sturgeon** program provides processes to ensure employees and/or sub-contractors are actively involved in the hazard identification process and hazards are reviewed with all employees concerned.

Employees are trained in the hazard identification process. Employees will be trained in the hazard identification process including the use and care of proper PPE.

Unsafe hazards must be reported immediately and addressed by the supervisor. The supervisor discusses the worksite hazard assessment with employees at the respective work location during the employee's documented orientation.

Review of Hazard Assessment

Existing worksite hazard identifications are formally reviewed annually or repeated at reasonably practicable intervals to prevent the development of unsafe and unhealthy working conditions and specifically updated when new tasks are to be performed that have not been risk assessed, when a work process or operation changes, before the construction of a new site or when significant additions or alterations to a job site are made.

The respective supervisor or project manager advises the Safety Manager when additional hazards are introduced into the work place in order to revise planning and assessment needs.

Risk Assessment

Hazards are classified and ranked based on severity. The program identifies hazards are classified/prioritized and addressed based on the risk associated with the task. (See the risk analysis matrix outlining severity and probability).



NC Sturgeon Safety Management System	Doc No:	HAZASID
	Initial Issue Date	02/2016
	Revision Date:	Initial Version
	Revision No.	0

HAZARD IDENTIFICATION AND ASSESSMENT			Next Revision Date:	TBD
Preparation: Safety Mgr	Authority: President	Issuing Dept: Safety	Page:	Page 3 of 7

NC Sturgeon RISK ASSESSMENT MATRIX

Severity	CONSEQUENCE				PROBABILITY				
	People	Assets	Environment	Reputation	A	B	C	D	E
					Not Done	Rarely	Once a week	Several Times in a Week	Multiple Times in a Day
0	No health effect	No damage	No effect	No impact					
1	Slight health effect	Slight damage	Slight effect	Slight impact					
2	Minor health effect	Minor damage	Minor effect	Limited impact					
3	Major health effect	Localized damage	Localized effect	Considerable impact					
4	Single fatality	Major damage	Major effect	National impact					
5	Multiple fatalities	Extensive damage	Massive effect	Global impact					

Key	Manage for continuous improvement (Low)	Incorporate risk reduction measures (Medium)	Intolerable (High)
-----	---	--	--------------------

Risk Controls/Methods to Ensure Identified Hazards Are Addressed and Mitigated

The following describes how identified hazards are addressed and mitigated:

- Risk assessed hazards are compiled with and addressed and mitigated through dedicated assignment, appropriate documentation of completion, and implemented controls methods including engineering or administrative controls and PPE required into the worksite hazard assessment of the site specific HSE plan. No work will begin before the worksite assessment is completed. Additionally, no risk assessed as High (Intolerable) shall be performed.
- If an existing or potential hazard to workers is identified during a hazard assessment **NC Sturgeon** must take measures to eliminate the hazard, or if elimination is not reasonably practicable, control the hazard. If reasonably practicable, **NC Sturgeon** must eliminate or control a hazard through the use of engineering controls. If a hazard cannot be adequately controlled using engineering controls, COMPANY must use administrative controls that control the hazard to a level as low as reasonably achievable. If the hazard cannot be adequately controlled using engineering and/or administrative controls, COMPANY must ensure that the appropriate personal protective equipment (PPE) is used by workers affected by the hazard. **NC Sturgeon** may use a combination of engineering controls, administrative controls, and personal protective equipment if there is a greater level of worker safety because a combination is used.

Emergency Control of Hazards

Only those employees competent in correcting emergency controls of hazards may be exposed to the hazard and only the minimum number of competent employees may be exposed during hazard emergency control. An example is a gas leak in a building. Only those personnel with training on fire safety, gas supply shut off and other



NC Sturgeon Safety Management System			Doc No:	HAZASID
			Initial Issue Date	02/2016
HAZARD IDENTIFICATION AND ASSESSMENT			Revision Date:	Initial Version
			Revision No.	0
			Next Revision Date:	TBD
Preparation: Safety Mgr	Authority: President	Issuing Dept: Safety	Page:	Page 4 of 7

related controls will attempt to resolve the emergency control of a hazard. **NC Sturgeon** will make every possible effort to control the hazard while the condition is being corrected or under the supervision of client emergency response personnel in every emergency.

Certification of Hazard Assessment

The Safety Manager completes and signs the certification of hazard assessment for the worksite hazard assessment (also see PPE Program) and includes it within the site specific HSE plan. Hazard assessments are reviewed annually and updated when new tasks are to be performed that have not been risk assessed.

Job Safety Analysis (JSA)

For those jobs with the highest injury or illness rates, jobs that are new to our operation, jobs that have undergone major changes in processes and procedures or jobs complex enough to require written instructions will have a Job Safety Analysis performed. Completed JSAs are available from the Safety Manager.

Site Specific HSE Plan (SSSP)

Each work location has a site specific HSE plan. Each employee reporting to a location shall receive a documented orientation from a **NC Sturgeon** supervisor that includes the SSSP for that site. The SSSP contains the COMPANY Health and Safety Policy, site specific safety requirements as well as a PPE matrix and a signed site specific worksite hazard assessment for that location, which the **NC Sturgeon** has a responsibility to provide.

Review Process

The hazard assessment program will be reviewed to ensure no new hazards derived from the corrective measures. The review shall include a management of change consideration as well.

The safety committee shall be involved in the review process as well.



NC Sturgeon Safety Management System		Doc No:	HAZASID
		Initial Issue Date	02/2016
HAZARD IDENTIFICATION AND ASSESSMENT		Revision Date:	Initial Version
		Revision No.	0
		Next Revision Date:	TBD
Preparation: Safety Mgr	Authority: President	Issuing Dept: Safety	Page: Page 7 of 7

INSTRUCTIONS FOR COMPLETING THE JOB SAFETY ANALYSIS FORM

Select an employee to help you with the JSA: someone who is experienced in the job, willing to help and a good communicator. The employees play an important role in helping you identify job steps and hazards. In summary, to complete this form you should consider the purpose of the job, the activities it involves, and the hazards it presents. In addition, observing an employee performing the job, or “walking through” the operation step by step may give additional insight into potential hazards. Here’s how to do each of the three parts of a Job Safety Analysis:

SEQUENCE OF BASIC JOB STEPS	POTENTIAL HAZARDS	RECOMMENDED ACTION OR PROCEDURE
<p>Examining a specific job by breaking it down into a series of steps or tasks, will enable you to discover potential hazards employees may encounter.</p> <p>Each job or operation will consist of a set of steps or tasks. For example, the job might be to move a box from a conveyor in the receiving area to a shelf in the storage area. To determine where a step begins or ends, look for a change of activity, change in direction or movement.</p> <p>Picking up the box from the conveyor and placing it on a hand truck is one step. The next step might be to push the loaded hand truck to the storage area (a change in activity). Moving the boxes from the truck and placing them on the shelf is another step. The final step might be returning the hand truck to the receiving area.</p> <p>Be sure to list all the steps needed to perform the job. Some steps may not be performed each time; an example could be checking the casters on the hand truck. However, if that step is generally part of the job it should be listed.</p>	<p>A hazard is a potential danger. The purpose of the Job Safety Analysis is to identify ALL hazards – both those produced by the environment or conditions and those connected with the job procedure. To identify hazards, ask yourself these questions about each step:</p> <p>Is there a danger of the employee striking against, being struck by, or otherwise making injurious contact with an object?</p> <p>Can the employee be caught in, by or between objects? Is there a potential for slipping, tripping, or falling?</p> <p>Could the employee suffer strains from pushing, pulling, lifting, bending, or twisting?</p> <p>Is the environment hazardous to safety and/or health (toxic gas, vapour, mist, fumes, dust, heat, or radiation)?</p> <p>Close observation and knowledge of the job is important. Examine each step carefully to find and identify hazards – the actions, conditions, and possibilities that could lead to an accident. Compiling an accurate and complete list of potential hazards will allow you to develop the recommended safe job procedures needed to prevent accidents.</p>	<p>Using the first two columns as a guide, decide what actions or procedures are necessary to eliminate or minimize the hazards that could lead to an accident, injury or occupational illness.</p> <p>Begin by trying to: (1) engineer the hazard out; (2) provide guards, safety devices, etc.; (3) provide personal protective equipment; (4) provide job instruction training; (5) maintain good housekeeping; (6) ensure good ergonomics (positioning the person in relation to the machine or other elements).</p> <p>List the required or recommended personal protective equipment necessary to perform each step of the job.</p> <p>Give a recommended action or procedure for each hazard.</p> <p>Serious hazards should be corrected immediately. The JSA should then be changed to reflect the new conditions.</p> <p>Finally, review your input on all three columns for accuracy and completeness with affected employees. Determine if the recommended actions or procedures have been put in place. Re-evaluate the job safety analysis as necessary.</p>